



NO	NAME OF PARTS	QTY	MATERIALS	SPECIFICATIONS
				JIS SPEC.
1	BODY	1	STAINLESS STEEL	SCS13A
2	COVER	1	STAINLESS STEEL	SCS13A
4	DISC	1	STAINLESS STEEL	SUS304
16A	NAME PLATE	1	ALUMINUM	A1050P
16B	WASHER	1	STAINLESS STEEL	SUS304
19	GASKET	1	NON-ASBESTOS SHEET	
33	COVER NUT	4	STAINLESS STEEL	SUS304 (8)
35	COVER BOLT	4	STAINLESS STEEL	SUS304 (B8)
82	SOCKET	1S	CARBON STEEL	S25C
216	FLOW DIRECTION PLATE	1	STAINLESS STEEL	SUS304
A	JACKET	1S	CARBON STEEL	STPG370+SS400
B	PLUG	1	CARBON STEEL	S25C

1S=1 SET

DIMENSIONS.

UNIT: mm

NOMINAL SIZE		d	H	L	l	END FLANGE					SOCKET								
mm	in.					FLANGE SIZE	D	BOLT HOLE			BOLT SIZE	g	t	f	S1	S2	SOCKET		
								C	NO.	h							P	NO.	J
15	1/2	15	73	160	6	40	140	105	4	19	M16	81	18	2	75	80	Rc1/2	3	10
20	3/4	20	73	160	7	40	140	105	4	19	M16	81	18	2	75	80	Rc1/2	3	10
25	1	25	73	194	7	50	155	120	8	19	M16	96	18	2	85	86	Rc1/2	3	15
40	1.1/2	40	90	218	14	65	175	140	8	19	M16	116	20	2	95	105	Rc1/2	3	25

STANDARD	FACE TO FACE OR END TO END	KITZ STANDARD
	END CONNECTION	JIS B2220 20K
	WALL THICKNESS	ASME B16.34 CLASS 300
	PRESSURE TEST	KITZ STANDARD
FIGURE		20UNAJ

20K CAST STAINLESS STEEL
LIFT CHECK VALVES

BOLTED COVER, JACKET TYPE, FLANGED ENDS.

DATE APPD	JAN.05.'09	DRAWING NO	△		
APPD BY	S. SANADA	964-A40004	△		
CHKD BY	Y. KONO		△		
DSGND BY	K. KOBAYASHI		△		
DRAWD BY	Y. NAKAYAMA		REV-06	MARK	DATE

KITZ CORPORATION

KITZ