



DIMENSIONS

UNIT: mm

NOMINAL SIZE		d	H	D1	L	END FLANGE							A	B	APPROX. MASS (kg)	
mm	in.					D	BOLT HOLE			g	(2)	f				
							c	NO.	h							BOLT SIZE
100	4	100	292	310	305	225	185	8	23	M20	160	31.8	2	65.5	165	55
150	6	150	374	360	403	305	260	12	25	M22	230	36.6	2	88.5	210	131
200	8	200	409	500	502	350	305	12	25	M22	275	41.3	2	134	377	199

NOTE (1) VALVE SIZE (inch) IDENTIFICATION.
 (2) *t* SHALL BE IN ACCORDANCE WITH ASME B16.5 CLASS 300.
 (3) ALLOWABLE SEAT LEAKAGE SHALL BE IN ACCORDANCE WITH ANSI/FCI 70-2 CLASS V.

NO	NAME OF PARTS	QTY	MATERIALS	SPECIFICATIONS
				JIS SPEC.
1	BODY	1	STAINLESS STEEL	SCS13A
2	BODY CAP	1	STAINLESS STEEL	SCS13A
3	STEM	1	STAINLESS STEEL	SUS630
4	BALL	1	STAINLESS STEEL	SUS304 OR SCS13A
7A	GLAND	1	STAINLESS STEEL	SCS13A
7B	GLAND	1	STAINLESS STEEL	SUS304
8	GLAND PACKING	1S	FLEXIBLE GRAPHITE	
16A	NAME PLATE	1	ALUMINUM	A1050P
16B	WASHER	1	CARBON STEEL	SS400
19	GASKET	1	FLEXIBLE GRAPHITE	
20	PACKING WASHER	1	STAINLESS STEEL	SUS316
30	BALL SEAT	2	CARBON+STAINLESS STEEL	SUS329J1
33	CAP NUT	1S	STAINLESS STEEL	SUS304 (8)
34A	GLAND NUT	1S	STAINLESS STEEL	
34B	NUT	1S	STAINLESS STEEL	
35	CAP BOLT	1S	STAINLESS STEEL	SUS304 (B8)
36	GLAND BOLT	1S	STAINLESS STEEL	
47	THRUST WASHER	1	CARBON	
67	STEM BEARING	1	CARBON	
92	CONNECTOR	1	CARBON STEEL	S45C
93	BRACKET	1	DUCTILE IRON	FCD450-10
99	BOLT	1S	CARBON STEEL	SS400
102	GEAR UNIT	1		
150	INNER RING	2	STAINLESS STEEL	
176	SEAT GASKET	2	FLEXIBLE GRAPHITE	
			1S=1 SET	

STANDARD	FACE TO FACE OR END TO END	ASME B16.10 CLASS 300
	END CONNECTION	JIS B2220 20K
	WALL THICKNESS	ASME B16.34 CLASS 300
	PRESSURE TEST	KITZ STANDARD
	FIGURE	G-20UTB3H

**20K CAST STAINLESS STEEL
BALL VALVES**

HIGH TEMPERATURE SERVICE. CARBOTITE SEAT.
 FULL BORE, GEAR TYPE, FLANGED ENDS.

DATE APPD	JUL. 21. '09	DRAWING NO	△		
APPD BY	S. SANADA	965-A40008	△		
CHKD BY	Y. ASAKAWA		△		
DSGND BY	S. KAJI		△		
DRAWD BY	Y. NAKAYAMA		REV-12	MARK	DATE

KITZ CORPORATION

KITZ